

Starlight 600TVL Bullet Camera NON OSD Version



Feature:

- 1/3" SONY Super HAD II CCD, Hitachi 14bit DSP
- Ultra High Resolution 600TV Lines
- Super Low Min. Illumination 0.00035Lux
- Aspherical 2.8-10mm Lens with Auto Iris
- Camera can always remain in color or automatically shift into B/W in low light conditions
- IP67 Waterproof level

Installation:

- To prevent shock or damage to the waterproof body, tighten all the screws and cover
- Adjust the visor to prevent the lens from direct sunlight
- Do not directly touch the front glass. To clean the dust, wipe with soft cloth with alcohol.
- Don't install it in the place where dithering and shake often
- Don't install it in the place where temperature is above 50°C or below -20°C
- Video line tie-in and DC tie-in must be avoided to touch water.
- If abnormal, please power off and contact the manufacturer

Note: Non-regulated power supply may cause camera damaged.

Technical Specifications:

Model No.	IV-HS8560VPD
Video System	NTSC/ PAL System
Sensor	1/3" SONY Super HAD II CCD, Hitachi 14bit DSP
Numbers of Pixel	NTSC: 768H*494V; PAL: 752H*582V
Resolution	600TVL
Lens	Aspherical 2.8-10mm Lens with Auto Iris
Day & Night	AUTO
Sync.	Internal
Scanning	2:1 Interlace
Signal Noise Ratio	50dB Min.
Electronic Shutter	NTSC: 1/60-1/120,000S; PAL: 1/50-1/120,000S
White Balance	Auto
Sense up	Auto
Backlight Compensation	On/ Off
Auto Gain Control	On/ Off
Gamma Correction	0.45
Video Output	1V p-p,75Ω
Min. Illumination	0.00035Lux
Waterproof	IP67
Voltage Input	DC12V±10%
Power Current	80mA
Operation Temp.	-20°C~50°C
Storage Temp.	-25°C~70°C
Humidity Range	20%~90% RH
Dimension	163L*60W*63H mm
Net Weight	500g