

Interkit



INTERKIT

Interkits, are available in one button and two button versions, the interkit forms a small intercommunicating system between 2 intercoms with an external call unit. The intercommunicating call is identified with an electronic tone and the external call unit with a buzzer. This feature provides an ideal solution for houses or offices which are on 2 different floors.

IK8K-1

One button door entry kit comprised of:

1 Outdoor station including a one call button speaker unit Art.8836I-1, flush mounting box with module support and hinge Art.8851 plus covering frame Art.886I. Standard finishes: mirror stainless steel for the front plate and aluminium for the module support.

2 Art.3002 3000 Series Smart line telephone with "Door open" and "Service" push buttons, buzzer call and electronic call tone with adjustable volume on 3 levels.

1 Art.321 Power Supply in a type A 3 module DIN box.

Packing: cardboard 30.5x29x7cm total weight 2.1 Kg.

IK8K-2

As IK8K-1 but two button version with 2 call push button speaker unit Art.8836I-2. The 2 intercoms are communicating but external calls are different for each phone. Packing: as above total weight 2.1 Kg

IK8K-1S, IK8K-2S

As door entry kits above but with surface mounting outdoor station. Packing: as above total weight 2.2 Kg.

For flush mounting outdoor station, a rainshield Art.8871 is available to install instead of the covering frame.

The module support, the module front plate and the rainshield are available in other finishes, see picture 2 on page 32 for available versions and additional suffix to use for orders.





