



## SCC-10KBIF

SANTEC 720p HD-CVI IR Outdoor Camera,  
3.6mm Fixlens, IR-LED 20m, 12 V DC

### PRODUCT DESCRIPTION

#### ► Application:

SANTEC compact day/night camera for indoor and outdoor applications, IP-66. Due to the built-in IR-LEDs (range: up to 20 m) and fix lens lens (3.6 mm), the camera is suitable for day as well as for night applications. The camera has an excellent resolution of 720p/25fps. The camera is delivered with a wall bracket with integrated cable management.

#### ► Technical specifications:

Type	Day/Night bullet camera
Video norm	HD-CVI
Sensor	1/2.9"
Sensor type	1/2.9" CMOS
Horizontal resolution (TVL)	720p
Effective pixel	1280(H) x 720(V)
Signal processing	Digital (DSP)
Synchronisation	Intern
Lens type	Fixlens
Focal length	3.6 mm
Angle of view (horizontal)	69°
IR cut filter	IR-Cut filter (mechanical)
Sensitivity (Lux)	0.01 / 0.0 lux
Automatic gain control (AGC)	AGC
Digital noise reduction (DNR)	2D
Video output	BNC, 75 Ohm 1 Vpp
Classification	IP-66

SANTEC BW AG  
An der Strusbek 31, 22926 Ahrensburg, Germany  
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10  
info@santec-video.com, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

### ► Technical specifications:

Vandal-proof	No
Housing colour	White
Housing material	Plastic
Integrated IR-LEDs	Yes
IR range (m)	up to 20
IR illumination angle (horizontal)	50 °
IR illumination angle (vertical)	30 °
IR wave length	850
Voltage	12 V DC
Power consumption (watt)	2
Operating temperature (°C)	-30 to +60
Rel. humidity (%)	30 - 90
Dimensions DxT (mm)	70 x 154
Weight	200 g
Identifier	CE
Specials	Coaxtransmission up to 500m, smart-IR

### ► Note:

The range of the built-in IR-LEDs strongly depend on the location and the surroundings. Strongly absorbent surfaces, e.g. dark, rough structures (floor, lawn or asphalt), may lead to a considerable reduction of the maximum range.

### ► Weitere Bilder:



### ► Recommended Accessories

VCA-12V-1.5ASA	SANTEC stabilized power supply unit 230V AC/12V DC, 1.5 A, with plug /adapter
KOAX-0.6/100	Coaxl cable 0.6/3.7, 75 Ohm for indoor usage, 100 m ring
SNPS-12D2	SANTEC stabilized power supply 12 V DC, 1.5 A, plug / adapter

SANTEC BW AG  
 An der Strusbek 31, 22926 Ahrensburg, Germany  
 Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10  
 info@santec-video.com, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.