

VTC-2612D

SANTEC discrete camera in smoke detection housing

PRODUCT DESCRIPTION

Application:

This colour camera in a smoke detection housing can be used for specially discrete applications. The camera has a wide angle lens of 3.7 mm and the power supply unit is included in the delivery.

Technical specifications:

_	
Туре	Color discrete camera
Video norm	PAL
Sensor	1/3"
Sensor type	Sony Super HAD CCD Chip
Horizontal resolution (TVL)	700
Effective pixel	752 (H) x 582 (V)
Signal processing	Digital (DSP)
Synchronisation	Intern
S/N ratio (dB)	> 48 dB
Lens type	Fix lens
Focal length	3.7 mm
Angle of view (horizontal)	67°
IR cut filter	No
Sensitivity (Lux)	0.05 Lux
Automatic gain control (AGC)	AGC
Digital noise reduction (DNR)	No
Video output	BNC, 75 Ohm 1 Vpp
Housing colour	White
Housing material	Plastic, Smoke detector housing

SANTEC BW AG

An der Strusbek 31, 22926 Ahrensburg, Germany Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10 info@santec-video.com, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

Technical specifications:

Voltage	12 V DC
Power consumption (watt)	1.2
Operating temperature (°C)	-10 to +50
Dimensions DxH (mm)	130x60
Identifier	CE

Recommended Accessories

VCA-12V-1.5ASA

SANTEC stabilized power supply unit 230V AC/12V DC, 1.5 A, with plug /adapter

SANTEC BW AG An der Strusbek 31, 22926 Ahrensburg, Germany Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10 info@santec-video.com, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.