



LE-24

Incorporated with advanced
OptiCom™ Technology, the LE-24 FHD
display sitting on a height adjustable
stand fits perfectly for home and office
applications.

AG Neovo's advanced OptiComTM Technology eliminates emission of harmful blue light and bothersome flicker to reduce eye fatigue and dryness when viewing the display constantly. The 24" LE-24 also features an IPS panel with full HD resolution and 20,000,000:1 contrast ratio for superior picture clarity and colour performance. Sitting firmly on a height adjustable stand, users are able to tilt, pivot, swivel and adjust the screen's height for optimized viewing comfort. All this and more make the LE-24 ideal for home and office multimedia applications.

- > 24" widescreen LED display
- > LED-backlit technology with high FHD 1920 x 1080 resolution
- > Advanced OptiComTM Technology: Anti-blue light and flicker free technologies for eye protection and viewing comfort
- > IPS panel provides consistent and accurate colour from all viewing angles
- > Slim housing design and widescreen format
- > Excellent clarity with ultrahigh 20,000,000:1 dynamic contrast ratio
- > Superior colour performance and colour contrast
- > HDMI input for Full HD connectivity with multimedia devices
- > Built-in speakers (2W x 2)
- > Height adjustable stand: tilt, pivot, swivel, height adjustable for multiple viewing options
- > Energy efficiency
- > VESA mount standard



LE-24

Specifications		LE-24
Panel	Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Surface Treatments Viewing Angle (H/V) Display Colour Response Time	LED-Backlit TFT LCD (IPS Panel) 23.6" FHD 1920 x 1080 0.272 x 0.272 250cd/m² (Typical) 20,000,000:1 (DCR) Hard Coating (3H) Anti-glare treatment 178°/178° 16.7M 7ms (GTG)
Frequency (H/V)	H.Freq V.Freq	30kHz – 83kHz 56Hz – 76Hz
Input	VGA DVI HDMI	15-Pin D-Sub 24-Pin DVI HDMI
Audio	Audio In Speaker	1 x stereo audio in for PC (audio jack, 3.5 Ø) 2W x 2
Power	Power Supply Power Requirements Consumption	Internal 100 – 240 V, 50-60 Hz < 35W (On) < 0.5W (Stand-by) < 0.5W (Off)
Operating Conditions	Temperature Humidity	0°C ~ 40°C (32°F ~ 104°F) 10% ~ 85%
Mounting	VESA FPMPMI	Yes (100 x 100mm)
Stand	Tilt Capacity Swivel Pivot Capacity Height Adjustment	-5° ~ 22° ±160° 0° ~ 90° 0 ~ 130 mm
Dimensions	with Base (W x H x D) w/o Base (W x H x D) Packaging (W x H x D)	571.4 x 554.7 x 244.5 mm (22.5" x 21.8" x 9.6") 571.4 x 350.9 x 48.1 mm (22.5" x 13.8" x 1.9") 694 x 443 x 180 mm (27.3" x 17.4" x 7.1")
Weight	Product Weight (with base) Product Weight (w/o base) Packaging Weight	5.6 kg (12.3 lbs) 3.3 kg (7.3 lbs) 7.3 kg (16.1 lbs)
Regulation Approval	Certifications & Compliance	CB, CE, RoHs, FCC, BSMI, WEEE
Accessories	Supplied	CD ROM (user manual), warranty card, power cord, 15-Pin D-Sub cable, Audio cable



 $\label{eq:Advanced} Advanced\ OptiCom^{\tiny{TM}}\ Technology:\ Anti-blue\ light\ and\ flicker\ free\ for\ a\ more\ comfortable\ viewing\ experience$



Built-in HDMI input makes the LE-24 easy to be paired with Full HD multimedia advices



IPS panel provides superb clarity from all angles



Ergonomically-designed stand allows users to tilt, pivot, swivel and adjust the height to its ideal position



