



LE-27

A spacious 27" LED display built on OptiCom[™] Technology and a practical height adjustment stand for home and office multimedia applications.

As eye protection is increasingly prioritized, the LE-27 is crafted with state-of-the-art OptiCom[™] Technology reducing the impact on eyes from the emissions of harmful blue light and disturbing flicker. Outstanding features also include an IPS panel, full HD resolution and HDMI input for better image clarity and enhanced rich colour to the multimedia lovers. Along with a height adjustable stand that is also able to tilt, pivot and swivel, the LE-27 justifies its competence for a wide variety of home and office applications.

- > 27" widescreen LED display
- > LED-backlit technology with high FHD 1920 x 1080 resolution
- > Advanced OptiComTM Technology: Anti-blue light and flicker free technologies for eye protection and viewing comfort
- > IPS panel provides consistent and accurate colour from all viewing angles
- > Slim housing design and widescreen format
- > Excellent clarity with ultrahigh 20,000,000:1 dynamic contrast ratio
- > Superior colour performance and colour contrast
- > HDMI input for Full HD connectivity with multimedia devices
- > Built-in speakers (2W x 2)
- > Height adjustable stand: tilt, pivot, swivel, height adjustable for multiple viewing options
- > Energy efficiency
- > VESA mount standard



OptiCom[™] Technology- Anti-blue light and flicker free technologies for eye protection and viewing comfort

LE-27

Specifications		LE-27
Panel	Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Surface Treatments Viewing Angle (H/V) Display Colour Response Time	LED-Backlit TFT LCD (IPS Panel) 27.0" FHD 1920 x 1080 0.311 x 0.311 300cd/m² (Typical) 20,000,000:1 (DCR) Hard Coating (3H) Anti-glare treatment 178°/178° 16.7M 7ms (GTG)
Frequency (H/V)	H.Freq V.Freq	30kHz – 83kHz 56Hz – 76Hz
Input	VGA DVI HDMI	15-Pin D-Sub 24-Pin DVI HDMI
Audio	Audio In Speaker	1 x stereo audio in for PC (audio jack, 3.5 Ø) 2W x 2
Power	Power Supply Power Requirements Consumption	Internal 100 – 240 V, 50-60 Hz < 40W (On) < 0.5W (Stand-by) < 0.5W (Off)
Operating Conditions	Temperature Humidity	0°C ~ 40°C (32°F ~ 104°F) 10% ~ 85%
Mounting	VESA FPMPMI	Yes (100 x 100mm)
Stand	Tilt Capacity Swivel Pivot Capacity Height Adjustment	-5° ~ 23° ±160° 0° ~ 90° 0 ~ 130 mm
Dimensions	with Base (W x H x D) w/o Base (W x H x D) Packaging (W x H x D)	645.3 x 569.3 x 244.5 mm (25.4" x 22.4" x 9.6") 645.3 x 398.6 x 56.4 mm (25.4" x 15.7" x 2.2") 765 x 501 x 224 mm (30.1" x 19.7" x 8.8")
Weight	Product Weight (with base) Product Weight (w/o base) Packaging Weight	8.2 kg (18.0 lbs) 5.6 kg (12.3 lbs) 10.7 kg (23.5 lbs)
Regulation Approval	Certifications & Compliance	CB, CE, RoHs, FCC, BSMI, WEEE
Accessories	Supplied	CD ROM (user manual), warranty card, power cord, 15-Pin D-Sub cable, Audio cable



Advanced OptiComTM Technology: Anti-blue light and flicker free for a more comfortable viewing experience



Built-in HDMI input makes the LE-27 easy to be paired with Full HD multimedia advices



IPS panel provides superb clarity from all angles



Ergonomically-designed stand allows users to tilt, pivot, swivel and adjust the height to its ideal position



