

AVerDiGi SA Series Hybrid and Real-Time Standalone DVR

# **Key Features**

- Plug and play, save your time assembling
- Hybrid DVR-support various IP and Analog cameras
- Support MegaPixel IP cameras
- Advanced MPEG4 and H.264 (S/W and H/W) compression
- Powerful remote software integration: CM3000, WebViewer, PDAViewer, 3GViewer, HandyViewer, and SmartViewer (for Symbian / Windows smart phone)
  - Temperature display panel
  - Backup to NAS / RAID and built-in DVD-RW
- Support up to 128 sensors in / relays out
- POS integration and advanced iPOS function
- Support more than 22 languages
- Support System Controller (Joystick Keyboard)
- Compact size to save maximal freightage



# AVerDiGi SA Series Hybrid and Real-Time Standalone DVR



### Anti-Virus

Embedded OS in DOM (disc on module), system can efficiently prevent virus attacking and operate even HDD crashed.



### Hybrid DVR

Support both IP and Analog cameras of most popular brands such as AXIS, SONY, Panasonic, Vivotek, ACTI, and etc.



# **HDD Saving**

MPEG4 and H.264 hardware compression can save about 4 times and 10 times storage size than MJPEG.



### Temperature Display

Temperature display LCD on the front panel to alert users when abnormal temperature detected.



### Attention Please

Enable dialogs to trace if operator pays attention to security monitor.



### Video Encryption

Encryption of video algorithms for privacy protection and security purposes.



### **Dual-Monitor**

Support dual-monitor environment for independent preview and playback or EMAP to save your trouble switching.



### TV-Out & Spot-Monitor

Provide multiple channels display on TV and pop up the channel once alarm triggered.



### **iEnhance**

iEnhance and iStable video processing software can fix shaking and jolts impact on video and enhance video quality for better image.



### **POS Integration**

Post transaction data and image for recording and search by keyword.



## **PDAViewer**

Provide video and audio monitoring on 4 channels or full screen view anytime and anywhere.



# CM3000/CM3000 Gold

Central Management System which supports live alarm notification, connection of 1000 DVRs in advanced mode, and compatible with AVerDiGi NV / SA / EB / NX / XR / SEB networking DVRs.

(support up to 4 monitors display)



# System Controller

Featured intuitive preview. playback, and PTZ control functions for users to efficiently control the surveillance system.



# Direct Burn

Built-in DVD-RW enables users to backup selected data to DVD / CD discs.

# **Application**









Sultable for different environment to use






**AVerDiGi** POS box

Various backup devices supported for every project's demand.

ATM



Com Port Expansion Device

Comport expansion card or box can support external comport devices up to 16

(Harris







Multiple launch programs to









Printer

Telephone Light







TV

Alarm







AVerDiGI.

Home Appliance

MMS











E-Mail Microphone Sensor





Drive

Pen

NAS

**AVerDiGi** RA4000e

Internet



Security guard can monitor and remote control DVR via CM3000 for Instant

# CM3000





For instant mutual regardless of distance



Enable users to monitor any time and everywhere via



WebViewer



PDAViewer/



HandyViewer/ SmartViewer



Remote Console



Users can integrate our system through 3rd party's intelligent software to customize their function, such as

- · Customized UI
- ATM system
- · Facial Recognition
- License Plate Recognition ....and more to meet your need.

# **Product Specifications**

	\$A5000			\$A6000E			SA7000H	
Item	SA5104	SA5108	SA5116	SA6208E	SA6216E	SA6416E	SA7208H	SA7416H
Operating system	Embedded O\$			Embedded OS			Embedded OS	
Video Format	H.264 / MPEG4 / MJPEG			H.264 / MPEG4			H.264 (Hardware Compression)	
Video input	4	8	16	8	16		8	16
Display rate (NTSC/PAL)	120/100 fps			240/200 fps	480/400 fps		240/200 fps	480/400 fps
Recording frame rate (CIF)	120/100 fps			240/2	200 fps 480/400 fps		240/200 fps	480/400 fps
Recording frame rate (VGA)	120/100 fps	00 tps 60/50 tps		240/200 fps	120/100 fps	240/200 fps	56/48 fps	112/96 fps
Recording frame rate (D1)	40/32 fps	tps 56/48 tps		240/200 fps	80/64 fps	160/128 fps	56/48 fps	112/96 fps
Audio input	4		8		6	8	16	
Sensor/Relay	Optional			4/4 (expandable)			4/4 (expandable)	
DVD-RW	Yes			Yes			Yes	
Removable HDD tray	2 HDD tray (support up to 3HDD)			2 HDD tray (support up to 3HDD)		D tray p to 4 HDD)	3 HDD tray (support up to 4 HDD)	
ром	2GB			2 GB			2 G8	
HDD pre-built (optional)	250GB/ 500GB/ 750GB/ 1TB			250GB/ 500GB/ 750GB/ 1TB			250GB/ 500GB/ 750GB/ 1TB	
Ethernet	RJ-45, 10/100/1000 Mbps			RJ-45, 10/100/1000 Mbps			RJ-45, 10/100/1000 Mbps	
USB 2.0	Front 2 ports, Rear 4 ports			Front 2 ports, Rear 4 ports			Front 2 ports, Rear 4 ports	
LCD Display	Temperature			Temperature			Temperature	
Dimensions (w x H x D)	290 x 160 x 480 mm			290 x 160 x 480 mm			290 x 160 x 480 mm	
Power	220 Watt			220 Watt			220 Watt	
Dual-monitor output	Optional			Yes			Yes	

Specifications are subject to change without prior notice

# **Product Illustration**































www.averdigi.com