


ACC™ ES 8-Port Appliance



Avigilon Control Center™ (ACC) ES 8-port (8P) Appliance is the latest innovative addition to the ACC ecosystem providing a cost effective, secure and flexible solution for smaller size deployments. With up to 8 TB of storage and a powerful on board PoE switch, the ACC ES 8P Appliance is an easy to deploy solution that can fit many needs. The ACC ES 8P Appliance features signed and encrypted Linux®-based firmware providing a secure and trusted platform for distributed and internet connected deployments.

KEY FEATURES

High capacity storage with 4 and 8 TB options

Provides up to 210 Mbps of total throughput

Configured and pre-licensed with 8 channels of Avigilon Control Center (ACC) ENT* video management software

Ready for mobile connections out of the box with web endpoint technology built in

Uses Avigilon's industry leading High Definition Stream Management (HDSM)™ technology


Remote alerts provide instant notifications to any mobile device

Ready to deploy out of the box with secure Linux-based firmware

Easily installed in a rack with an optional rack-mounted tray with sliding rail system

^{*} Platform limitations apply, please consult your sales engineer.

Outline Dimensions



Specifications

VMA-ENVR1-8Px-NA =

SYSTEM	HDD Storage	1 x 3.5 inch Serial ATA hard drive (4 or 8TB)
	Recording Rate	130 Mbps
	Stream Out Rate	80 Mbps
	PoE+ Ports	8 x 10/100 Mbps
	Total PoE Budget	120 W
	Uplink	2 x 1 GbE
	External I/O Terminals	4 digital inputs and 4 relay outputs
MECHANICAL	Dimensions (LxWxH)	195 x 325 x 42 mm; 7.67 x 12.79 x 1.65 in
	Welght	2.8 kg (unit); 6.17 lbs
ELECTRICAL	System Power Input	100-240VAC; 2.5A; 50-60Hz
	Power Supply	Single external, 54V
	Power Consumption	40W minimum; 180W maximum
ENVIRONMENTAL	Operating Temperature	0° C to 40° C (32° F to 104° F)
	Storage Temperature	-20° C to 60° C (-4° F to 140° F)
	Humidity	0 - 90% relative humidity (non-condensing)
CERTIFICATIONS	Certifications/Directives	UL, cUL, CE, RoHS, WEEE, RCM, NOM
	Safety	UL 60950-1, CSA 60950-1, IEC/EN 60950-1
	Electromagnetic Emissions	FCC Part 15 Subpart B Class B, IC ICES-003 Class B, EN 55032 Class B, EN 61000-6-3, EN 61000-3-2, EN 61000-3-3
	Electromagnetic Immunity	EN 55024, EN 61000-6-1
SUPPORTED ACC FEATURES	System	8 cameras / device 10 client connections / device
		 Site support for up to 24 servers, 500 cameras and 100 defined users
	Device Support	 Automatic device discovery Avigilon HD H.264 Pro cameras Avigilon HD H.264 cameras & encoders (up to 8) ONVIF® compliant cameras & encoders
	Client	 Saved Views Maps Intelligent Virtual Matrix Web pages Collaborative investigations
	Recording, Searching and Playback	 Hourly configurable recording schedule Lossless recording Intelligent motion search Live export Multi-camera export
	Integrations	All 3rd party integrations via the ACC SDK Plus: CommScope iPatch® DDS Amadeus 5 RS2 Accessit! DDS Amadeus 5
	Additional Features	 Email event notification Digital input email trigger Manual digital output trigger Audio recording and talkdown Unlimited rule triggers Redundant recording Fallover connections Alarm escalation
ORDERING INFORMATION	VMA-ENVR1-8P4	ACC ES 8-Port Appliance, 4TB
	VMA-ENVR1-8P8	ACC ES 8-Port Appliance, 8TB
	ENC-4P-H264	4-Port H.264 Video Encoder with 4 Audio Inputs and 4 Audio Outputs
	PS-180W-ENVR1-8P	External Power Supply, ES 8P Appliance, 180W, No power cord
	RMS1U -A-ENVR1-8P	Rackmount Shelf with Sliding Rails for ES 8P Appliance

VMA-ENVR1-8Px-UK =

VMA-ENVR1-8Px-EU =

VMA-ENVR1-8Px-AU =