

HomeSiren Fibra

Wired indoor siren



The device is compatible only with hubs supporting Fibra protocol. Find the detailed information by QR code or the link:



https://ajax.systems/support/devices/homesiren-fibra/






HomeSiren Fibra is the device of the new Fibra wired product line. Such devices can only be purchased, installed and administered by accredited Ajax partners.



Adjustable alarms and notifications volume level: from 81 to 105 dB



Adjustable alarm duration: from 3 to 180 seconds




LED indication of security mode




Output for connecting an external LED indicator




Chime feature




Arming and delays notifications





communication technology




Fibra is a **two-way wired protocol**, ensuring fast and secure communication between hubs and devices. Based on a **bus connection method**, Fibra delivers instant data-rich alarms: security companies and users know which device was triggered, when and where it happened.

Fibra features **encryption** and **authentication** to prevent forgery, as well as **polling** to display device's status in real time. Supporting **up to 2,000 m** of wired connectivity, Fibra is ready to protect any facilities, and deliver **the best user experience** for both end users and installers.

System features



Bus connection method with hub



Up to 2,000 m of two-way encrypted communication



Hub polls connected devices with the lowest possible frequency



Pairing via QR code or bus scanning



Configuring via a smartphone or desktop app



Tampering alarm notification

Technical specifications

Compliance with standards	EN 50131 (Grade 2) PD 6662:2017	Compatibility	Hub Hybrid (2G) Hub Hybrid (4G)
			Range extenders no
Features	Type of notifications Acoustic and LED	Opening detection	Fibra communication technology
	Alarm volume from 81 to 105 dB at a distance of 1 m Set by admin in the app		Communication range up to 2,000 m with U/UTP cat.5 4×2×0,51 cable
	Alarm duration from 3 to 180 seconds Set by admin in the app		Polling interval 12–300 sec Set automatically

Features	Built-in siren operating frequency 3.4 ± 0.5 kHz		
	Additional LED connection Available, 3 V		
Power supply	24 V≕, up to 50 µA	Installation	Operating temperature range from -10°C to +40°C
			Operating humidity up to 75%
			Ingress protection IP50
Casing	Colour white, black	Complete set	HomeSiren Fibra SmartBracket Installation kit
	Dimensions 90,5 × 90,5 × 33 mm		Quick Start Guide
	Weight 84 g		
	Tampering alarm yes		