

# Day/Night 20x HD PTZ Dome Cameras



Avigilon's end-to-end surveillance solutions deliver image detail no other system can match. Avigilon™ Control Center software, featuring High Definition Stream Management (HDSM)™ technology combined with our broad range of megapixel cameras (from 1 MP to 29 MP) provide unprecedented clarity—while effectively managing storage and bandwidth requirements. Our components are scalable and can work together in an end-to-end system, or can be customized to create your own powerful and cost-effective solution.

The innovative HD PTZ camera is just one way Avigilon can help provide the very best monitoring and protection.



Avigilon's HD PTZ camera offers unsurpassed image quality with precise positioning and predictable high-speed tracking. Underpinned by the H3 platform, the HD PTZ camera takes advantage of enhanced High-Definition Stream Management™ technology to lower bandwidth and storage requirements, while providing incredible low light performance. The camera features a 20x optical zoom with up to 12x digital zoom, and provides continuous 360° degree rotation at up to 450° per second. The unique design of the in-ceiling variant mount allows for simple installation in just seconds and makes it an ideal camera for indoor applications in retail, casino and commercial environments. The pendant variant is targeted specifically at indoor and outdoor expansive areas with manned operations, such as large retail chains, airports, petrochemical, casinos and city surveillance.

## KEY FEATURES

|   |
|---|
| Progressive scan CMOS sensor  |
| Easily track targets with 360 degree endless rotation   |
| Able to move at up to 450 degrees per second  |
| 4.7-94 mm, F1.6 lens with 20x zoom  |
| Provides smooth operation and captures fluid motion at 30 frames per second                   |
| H.264 and Motion JPEG compression   |
| ONVIF compliant API   |
| Hide sensitive areas with 3D privacy mask   |
| Automatic exposure control and iris control   |
| Automatic removable IR cut filter for IR sensitivity at night                                 |
| Power over Ethernet, 24 VAC or 24 VDC power input   |
| External microphone and speaker support for two-way audio                                     |
| External I/O interface for connecting alarms and relays                                       |
| Pendant variant supports broad environmental conditions for challenging outdoor installations |


# Specifications

HD PTZ CAMERAS

|                          | IN-CEILING PTZ DOME CAMERA |  |                    |                     | PENDANT PTZ DOME CAMERA   |  |              |               |                           |     |
|--------------------------|----------------------------|--|--------------------|---------------------|---|--|--------------|---------------|---------------------------|-----|
| <b>IMAGE PERFORMANCE</b> | Image Sensor               | WDR 1/2.8" progressive scan CMOS   |                    |                     |   |  |              |               |                           |     |
|                          | Active Pixels              | 1.0 MP:  | 1280 (H) x 720 (V) |                     | 2.0 MP:   | 1920 (H) x 1080 (V)                              |              |               |                           |     |
|                          | Imaging Area               | 4.8 mm (H) x 2.7 mm (V); 0.189" (H) x 0.106" (V)   |                    |                     |   |  |              |               |                           |     |
|                          | Minimum Illumination       | 0.4 lux (F1.6) in color mode; 0.04 lux (F1.6) in monochrome mode   |                    |                     |   |  |              |               |                           |     |
|                          | Dynamic Range              | 100 dB   |                    |                     |   |  |              |               |                           |     |
|                          | Image Rate                 | 30 (all resolutions)   |                    |                     |   |  |              |               |                           |     |
|                          | Resolution Scaling         | Down to 352 x 240  |                    |                     |   |  |              |               |                           |     |
| <b>LENS</b>              | Lens                       | 47-94 mm, 20x zoom, F1.6 and automatic focus   |                    |                     |   |  |              |               |                           |     |
|                          | Angle of View              | 2.9° - 55.2°   |                    |                     |   |  |              |               |                           |     |
| <b>IMAGE CONTROL</b>     | Image Compression Method   | H.264 (MPEG-4 Part 10/AVC), Motion JPEG  |                    |                     |   |  |              |               |                           |     |
|                          | Streaming                  | Multi-stream H.264 and Motion JPEG   |                    |                     |   |  |              |               |                           |     |
|                          | Motion Detection           | Selectable sensitivity and threshold   |                    |                     |   |  |              |               |                           |     |
|                          | Electronic Shutter Control | Automatic, Manual (1/6 to 1/8000 sec)  |                    |                     |   |  |              |               |                           |     |
|                          | Iris Control               | Automatic, Manual  |                    |                     |   |  |              |               |                           |     |
|                          | Day/Night Control          | Automatic, Manual  |                    |                     |   |  |              |               |                           |     |
|                          | Flicker Control            | 50 Hz, 60 Hz   |                    |                     |   |  |              |               |                           |     |
|                          | White Balance              | Automatic, Manual  |                    |                     |   |  |              |               |                           |     |
|                          | Backlight Compensation     | Adjustable   |                    |                     |   |  |              |               |                           |     |
|                          | Privacy Zones              | Up to 64 zones, 3D privacy mask supported  |                    |                     |   |  |              |               |                           |     |
|                          | Presets                    | 100 named presets  |                    |                     |   |  |              |               |                           |     |
|                          | Tours                      | 10 named guard tours   |                    |                     |   |  |              |               |                           |     |
|                          | Audio Compression Method   | G.711 PCM 8 kHz  |                    |                     |   |  |              |               |                           |     |
|                          | Audio Input/Output         | Line level input and output  |                    |                     |   |  |              |               |                           |     |
|                          | Video Output               | NTSC/PAL   |                    |                     |   |  |              |               |                           |     |
| External I/O Terminals   | Alarm In, Alarm Out        |  |                    |                     |   |  |              |               |                           |     |
| <b>NETWORK</b>           | Network                    | 100BASE-TX   |                    |                     |   |  |              |               |                           |     |
|                          | Cabling Type               | CAT5   |                    |                     |   |  |              |               |                           |     |
|                          | Connector                  | RJ-45  |                    |                     |   |  |              |               |                           |     |
|                          | API                        | ONVIF compliance version 1.02, 2.00, Profile S ( <a href="http://www.onvif.org">www.onvif.org</a> )                                |                    |                     |   |  |              |               |                           |     |
|                          | Security                   | Password protection, HTTPS encryption, digest authentication, WS authentication, user access log, 802.1x port based authentication |                    |                     |   |  |              |               |                           |     |
|                          | Protocol                   | IPv4, HTTP, HTTPS, SOAP, DNS, NTP, RTSP, RTCP, RTP, TCP,UDP, IGMP, ICMP, DHCP, Zeroconf, ARP, LLDP                                 |                    |                     |   |  |              |               |                           |     |
|                          | Streaming Protocols        | RTP/UDP, RTP/UDP multicast, RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/RTSP/HTTPS/TCP, HTTP  |                    |                     |   |  |              |               |                           |     |
| <b>MECHANICAL</b>        | Dimensions (ØxH)           | 232 mm x 222.44 mm; 9.134" x 8.757"  |                    |                     | 226 mm x 299.77 mm; 8.9" x 11.8"  |  |              |               |                           |     |
|                          | Weight                     | 2.18 kg (4.85 lbs)   |                    |                     | 3.9 kg (8.6 lbs)  |  |              |               |                           |     |
|                          | Dome Bubble                | Acrylic, clear   |                    |                     |   |  |              |               |                           |     |
|                          | Body                       | Plastic, plenum rated (UL 2043)  |                    |                     | Aluminum  |  |              |               |                           |     |
|                          | Housing                    | Recessed mount   |                    |                     | Pendant mount   |  |              |               |                           |     |
|                          | Finish                     | Plastic, RAL 9003  |                    |                     | Powder coat, cool gray 2  |  |              |               |                           |     |
|                          | Tilt                       | 186°, E-flip, 0.05 - 360°/sec  |                    |                     |   |  |              |               |                           |     |
|                          | Pan                        | 360°, endless, 0.05 - 450°/sec   |                    |                     |   |  |              |               |                           |     |
| <b>ELECTRICAL</b>        | Power Consumption          | 55 W   |                    |                     | PoE: IEEE 802.3at Class 4 PoE Plus compliant  |  |              |               |                           |     |
|                          | Power Source               | VDC: 24 V +/- 10%  |                    |                     | VAC: 24 V +/- 10%   |  |              |               |                           |     |
|                          |                            | 25.5 W with IEEE 802.3at Class 4 PoE Plus  |                    |                     |   |  |              |               |                           |     |
|                          | Power Connector            | 2-pin terminal block   |                    |                     | Waterproof 2-pin connector  |  |              |               |                           |     |
| <b>ENVIRONMENTAL</b>     | Operating Temperature      | -10 °C to +50 °C (14 °F to 122 °F)   |                    |                     | -45 °C to +50 °C (-50 °F to 122 °F) with external power<br>-30 °C to +50 °C (-22 °F to 122 °F) with IEEE 802.3at Class 4 PoE Plus power |  |              |               |                           |     |
|                          | Storage Temperature        | -10 °C to +70 °C (14 °F to 158 °F)   |                    |                     |   |  |              |               |                           |     |
|                          | Humidity                   | 0 - 95% non-condensing   |                    |                     |   |  |              |               |                           |     |
| <b>CERTIFICATIONS</b>    | Safety                     | UL 60950   | CSA 60950          | CB Scheme           | RCM   | UL 60950   | CSA 60950    | CVV           | CB Scheme                 | RCM |
|                          | Environment                |  |                    |                     |   | IK10 Impact Rating (with H3PTZ-DP-CLEAR-IK only) |              |               | Meets IP66 Weather Rating |     |
|                          | Electromagnetic Emissions  | FCC Part 15 Subpart B Class B  |                    | IC ICES-003 Class B |   | EN 55022 Class B                                 |              | EN 61000-6-3  |                           |     |
|                          | Electromagnetic Immunity   | EN 55024   | EN 61000-4-2       | EN 61000-4-3        | EN 61000-4-4  | EN 61000-4-5                                     | EN 61000-4-6 | EN 61000-4-11 | EN 61000-6-1              |     |


# Outline Dimensions

## In-Ceiling PTZ Dome Camera



|       |        |
|-------|--------|
| [X.X] | INCHES |
| X     | MM     |

## Pendant PTZ Dome Camera



# Ordering Information

### IN-CEILING PTZ DOME CAMERAS

|                 |   |
|-----------------|---|
| 1.0W-H3PTZ-DC20 | 1.0 Megapixel Day/Night H.264 20x HD PTZ In-Ceiling Dome Camera |
| 2.0W-H3PTZ-DC20 | 2.0 Megapixel Day/Night H.264 20x HD PTZ In-Ceiling Dome Camera |
| H3PTZ-DC-CLEAR  | PTZ In-Ceiling Dome Camera Cover with Clear Bubble              |
| H3PTZ-DC-SMOKE  | PTZ In-Ceiling Dome Camera Cover with Smoked Bubble             |
| H3PTZ-DC-PNL    | Metal Ceiling Panel   |

### PENDANT PTZ DOME CAMERAS

|                   |  |
|-------------------|--|
| 1.0W-H3PTZ-DP20   | 1.0 Megapixel Day/Night H.264 20x HD PTZ Pendant Dome Camera |
| 2.0W-H3PTZ-DP20   | 2.0 Megapixel Day/Night H.264 20x HD PTZ Pendant Dome Camera |
| MNT-PEND-WALL     | Indoor/Outdoor Pendant Mount Bracket                         |
| MNT-AD-POLE-B     | Pole Mounting Bracket  |
| MNT-AD-CORNER     | Corner Mounting Bracket                                      |
| H3PTZ-DP-SMOKE    | Dome Camera Cover with Smoked Bubble                         |
| H3PTZ-DP-CLEAR-IK | Dome Camera Cover with Clear Bubble (IK10)                   |